

Примеры

- Сложный фильтр
- Ожидание загрузки всех скриптов

Сложный фильтр

```
const leads = await Global.ns._clients.app._leads.search()

.where((f, g) => {
  let opperands: Filter[] = [];
  opperands.push(f.__deletedAt.eq(null));
  opperands.push(f.__createdAt.gte(Context.data.start_date!));
  opperands.push(f.__createdAt.lte(Context.data.end_date!));
  if (Context.data.status?.length) {
    let filterStatus: Filter[] = [];
    for (const adress of Context.data.adresses) {
      filterStatus.push(f._address.eq(adress))
    }
    opperands.push(g.or(...filterStatus))
  }
  if (Context.data.companyes?.length) {
    let filterChannel: Filter[] = [];
    for (const company of Context.data.companies) {
      filterChannel.push(f._companies.link(company))
    }
    opperands.push(g.or(...filterChannel))
  }
  return g.and(...opperands)
})

.size(10000)

.all()
```

Ожидание загрузки всех скриптов

```
$(function() {  
  // Загрузка внешних скриптов  
  const loadScript = url => new Promise(resolve => {  
    const script = document.createElement('script')  
    script.addEventListener('load', () => {  
      resolve()  
    })  
    script.src = url  
    document.body.append(script)  
  })  
  
  const srcIndex = loadScript('https://cdn.amcharts.com/lib/5/index.js')  
  const srcXY = loadScript('https://cdn.amcharts.com/lib/5/xy.js')  
  const srcAm = loadScript('https://cdn.amcharts.com/lib/5/themes/Animated.js')  
  
  Promise.all([srcIndex, srcXY, srcAm])  
    .then(([srcIndex, srcXY, srcAm]) => {  
      console.log('Скрипт index.js загружен')  
      console.log('Скрипт ху.js загружен')  
      console.log('Скрипт Animated.js загружен')  
      amLoadScript()  
    })  
  
  function amLoadScript() {  
    //  
  }  
});
```